




# PRO-203L LIQUID FILLED U-CLAMP PANEL MOUNT

Improved accuracy to ASME B40.1 Grade A. One piece design for toughness during installation. Glycerin filled for added durability during in application. Stainless steel case and bezel with copper alloy internals.

2	<b>Dial</b>	2 1/2" (63 mm),
	<b>Case</b>	Stainless steel, glycerine filled
	<b>Wetted Parts</b>	Copper alloy
	<b>Bezel</b>	Stainless steel, fixed
	<b>Lens</b>	Polycarbonate
	<b>Pointer</b>	Black aluminum
	<b>Connection</b>	Center back mount with u-clamp 2 1/2" dial = 1/4" NPT
	<b>Scale</b>	Standard: psi/BAR (x 100 = kPa)
	<b>Accuracy</b>	2-1-2% of span ASME B40.1 Grade A
	<b>Ambient Temp</b>	Glycerine Filled = 30° F to 160° F Dry = -30° F to 180° F



Design meets or exceeds ASME B40.100 pressure gauge standard.



- Certificate of Accuracy, NIST traceable
- Custom Dial
- Liquid Fill Options, see page 180
- Anti-Vibration Movement, see page 113
- Dry, Fillable Case
- Special Connection Size
- Max/Min Pointer, see page 126

\*Lead times/minimums may apply

Dial	Unit	A	B	C	D	E	F	G
2 1/2"	In.	2.65"	1.21"	0.91"	2.12"	1/4"	3.84"	2.44"
	mm	68	31	23	54	NPT	98	61

Dial Size	Est. Unit Weight	Box Qty
2 1/2"	0.55 lbs (0.26 kg)	60

NOTE: Because of continuing improvements, increments/specifications are subject to change without notice. Stock ranges vary by dial size and configuration. Consult PIC Gauges for availability.